

DATA SHEET

SFP+ 10G DWDM 80KM I-TEMP TRANSCEIVER

DESCRIPTION

This transceiver is Multi-Vendor MSA Compatible SFP+ (Small Form factor Pluggable), operating over pair of single mode fiber (SMF) for 80Km DWDM application. This transceiver uses top quality EML Laser transmitter with operating at specific wavelength in ITU-T DWDM Grid 100 GHz C-Band and PIN Photodiode receiver. It supports DDM optical diagnostics and operates in Industrial temperature range (-40°/+85°C).



KEY FEATURES

Up to 10.3Gb/s bi-directional data links

100GHz ITU Grid, C-Band

Up to 80km on 9/125µm SMF

Electrical interface specifications per SFF-8431

Management interface specifications per SFF-8431 and SFF-8472

SFP+ MSA package with duplex LC connector

DWDM-rated EML Transmitter

Single +3.3V power supply

Class 1 laser safety certified

Operating temperature: 0°C to +70°C commercial, and -40°C to +85°C industrial

RoHS Compliant

APPLICATIONS

10G Ethernet 10GBASE-ZR/ZW

80km 10G DWDM Network

COMPLIANCES

Compliant to SFF-8402, SFF-8432.

Compliant to IEEE802.3ba

DDM Compliant with SFF-8472 SFP+ MSA.

RoHS Compliant6

DATA SHEET

SFP+ 10G DWDM 80KM I-TEMP TRANSCEIVER

ENVIRONMENTAL SPECIFICATIONS

Parameter	Min.	Typ.	Max.	Unit
Operation Temperature	-40		+85	°C
Storage Temperature	-40	-----	+85	°C
Operation Humidity*	5	-----	85	%
Storage Humidity	5	-----	85	%

(*) not condensing

OPERATING SPECIFICATIONS

Parameter	Min.	Typ.	Max.	Unit
Supply Voltage	3.135	+3.3	+3.465	V
Power Dissipation			1.8	W
Transmission Distance			80	Km

OPTICAL SPECIFICATIONS

TRANSMITTER

Parameter	Min.	Typ.	Max.	Unit
Wavelength	1528.77	-	1563.86	nm
Average Optical Power	0		4	dBm
Optical Modulation Amplitude, 25GE	-2			dBm
Side Mode Suppression Ratio	30			dB
Extinction Ratio (ER)	9			dB
Transmitter and Dispersion Penalty			3	dB
Optical Return Loss Tolerance			21	dB

RECEIVER

Parameter	Min.	Typ.	Max.	Unit
Input Wavelength	1528	-	1565	nm
Receiver Sensitivity			-23	dBm
OSNR	27			dB
Max OSNR Path Penalty			4	dB
LOSA	-35			dBm
LOSD			-25	dBm
Hysteresis	0.5			dB

DATA SHEET

SFP+ 10G DWDM 80KM I-TEMP TRANSCEIVER

ORDERING INFORMATION

Jabil Part Number	Package	Rate	Reach	Other info
JPSP10ZRLCI000Dxx	SFP+	10G	80Km	DDM/RoHS

xx = channel number (100GHz grid)

CONTACT INFORMATION

For additional information and evaluation samples order, please contact:

Chuck Sinha, Sr. Director of Sales

Jabil Photonics

5960 Inglewood Dr. Suite 100, Pleasanton, CA

Mobile: 408-505-0955 Email: Chuck_Sinha@Jabil.com