

## DATA SHEET

# SFP28 25G LR, 1310NM SMF TRANSCEIVER

## DESCRIPTION

This transceiver is designed for 24.33Gbps and 25.78Gbps data rate over SMF and support up to 10km link length. Digital Diagnostic Monitoring interface is available via an I2C interface.



## KEY FEATURES

---

Compatible with CPRI option10 24.33Gbps and 25GBASE 25.78Gbps

---

Up to 10km transmission on SMF

---

1310nm DML laser transmitter

---

SFP28 MSA compliant

---

Built-in digital diagnostic functions

---

Single +3.3V power supply

---

Operating case temperature: 0 to +70 °C

---

RoHS 6 Compliant

---

## APPLICATIONS

---

25GBASE-LR

---

24.33Gbps CPRI

---

## COMPLIANCES

---

Compliant to SFF-8402, SFF-8432.

---

Compliant to IEEE802.3ba

---

DDM Compliant with SFF-8472 SFP+ MSA.

---

RoHS Compliant6

---

## DATA SHEET

# SFP28 25G LR, 1310NM SMF TRANSCEIVER

### ENVIRONMENTAL SPECIFICATIONS

Parameter	Min.	Typ.	Max.	Unit
Operation Temperature	0		+70	°C
Storage Temperature	-40	-----	+85	°C
Operation Humidity*	5	-----	85	%
Storage Humidity	5	-----	85	%

(\*) not condensing

### OPERATING SPECIFICATIONS

Parameter	Min.	Typ.	Max.	Unit
Supply Voltage	3.135	+3.3	+3.465	V
Power Dissipation			1.2	W
Transmission Distance			10	Km

### OPTICAL SPECIFICATIONS

#### TRANSMITTER

Parameter	Min.	Typ.	Max.	Unit
Wavelength	1295	1310	1325	nm
Average Optical Power	-4.5		2.5	dBm
Optical Modulation Amplitude, 25GE	-2			dBm
OMA-TDP, 25GE	-3			dBm
Transmitter OFF Output Power			-30	dBm
Side Mode Suppression Ratio	30			dB
Extinction Ratio (ER)	3.5			dB
Transmitter and Dispersion Penalty			2.7	dB
Optical Return Loss Tolerance			11	dB

#### RECEIVER

Parameter	Min.	Typ.	Max.	Unit
Input Wavelength	1260	1310	1355	nm
Stressed OMA Sensitivity, 25GE			-8.3	dBm
OMA Sensitivity, 25GE@1E-12			-9.6	dBm
Average Rx Sensitivity, 25GE@1E-12			-11.4	dBm
Receiver Overload	2.5			dBm
Receiver Reflectance			-26	dB
LOSA	-30		-17	dBm
LOSD			-17	dBm
Hysteresis	0.5			dB



## DATA SHEET

# SFP28 25G LR, 1310NM SMF TRANSCEIVER

### ORDERING INFORMATION

Jabil Part Number	Package	Rate	Reach	Other info
JPS825LRLCC000L13	SFP28	25G	10Km	DDM/RoHS

### CONTACT INFORMATION

**For additional information and evaluation samples order, please contact:**

**Chuck Sinha, Sr. Director of Sales**

Jabil Photonics

5960 Inglewood Dr. Suite 100, Pleasanton, CA

Mobile: 408-505-0955 Email: [Chuck\\_Sinha@Jabil.com](mailto:Chuck_Sinha@Jabil.com)